

Project: \_\_\_\_\_  
 Duct System: \_\_\_\_\_  
 Drawing Numbers: \_\_\_\_\_

Contractor: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Date Submitted: \_\_\_\_\_

**Pressure Class:**

- SMACNA 2005 Pos 10" wg
- SMACNA 2005 Neg 2" wg
- SMACNA 2005 Neg 4" wg
- SMACNA 2005 Neg 6" wg
- SMACNA 2005 Neg 10" wg
- Other per spec

**Material Type:**

- Galvanized
- Paint Grip
- Aluminum 3003
- 304 Stainless
- 316 Stainless
- 4x1 PVC Coated
- 4x4 PVC Coated

**Joints:**

- Couplings up to \_\_\_\_\_
- LaPineFlange (T-24)
- Vanstone Angle Ring - Fittings
- Stitch Welded Angle Ring - Pipe
- Fully Welded Angle Ring - Pipe
- Raw (butt weld in field)
- Other (specify below)

**Fitting Construction:**

**Circumferential Seams:**

- standing seam up to 40"
- seam welded

**Longitudinal Seams:**

- stitch welded
- seam welded
- tig welded (min 8")

**Pipe Construction:**

- Spiral (smooth)
- Spiral (corrugated) Dia: \_\_\_\_\_
- Long Seam

**Maximum Pipe Length:**

- 10' (default)
- Other (specify): \_\_\_\_\_

**Branch Type:**

- Straight
- Conical
- Shoe (boot)
- Lateral
- Conical Lateral

**Rectangular Taps:**

**Loose:**

- Straight 4" length std
- Straight - Specify length: \_\_\_\_\_
- 45 Deg Entry 5" length std
- 45 Deg Entry - Specify length: \_\_\_\_\_

**Installed:**

- Straight 4" length std
- Straight - Specify length: \_\_\_\_\_
- 45 Deg Entry 5" length std
- 45 Deg Entry - Specify length: \_\_\_\_\_

**Branch/Tap Options:**

- Full Bodied Fittings
- Manifolder Taps
- Loose Taps

**Additional Notes:**
