



# CLAMP-STYLE DUCT

## FAST. FLEXIBLE. EFFICIENT.

CHEETAHDUCT is a US engineered and manufactured clamp-style duct with an adjustable sleeve. Our innovative adjustable sleeve allows for fast and adaptable industrial dust collection system design and installation.

Components undergo end forming to create a perfectly pressed rolled edge suitable for a precision joint connection. Each joint is then tightly secured by an external gasketed clamp. Our use of Rolled Edge Pipe, in conjunction with our Adjustable Sleeve, allows for unlimited design flexibility.

CHEETAHDUCT is easy to disassemble and reassemble for cleaning, maintenance, or reconfiguration. This connection system will eliminate the need for sealants, rivets or screws, making CHEETAHDUCT a snap to install.

Our Adjustable Sleeve with O-Ring will save you time, money, and maintain the integrity of each joint connection seal. The current methods are time consuming and often result in a joint which is not completely sealed. All of our CHEETAH sleeves are shipped assembled with an O-Ring.

## APPLICATIONS

Any industrial collection system conveying dry dust or smoke

## INDUSTRIES

- Agriculture
- Automotive
- Food processing
- Paper
- Pharmaceutical
- Plastics
- Recycling
- Textiles
- Welding and metal fabrication
- Wood working

## ADVANTAGES

- Less joint connections
- Lighter weight
- Fast installation
- Fast inspections
- More design flexibility
- Easier system configuration
- No tools, screws, or messy sealants required

For more information, call 269.388.5900  
or visit [CHEETAHDUCT.com](http://CHEETAHDUCT.com).

MADE IN THE U.S.A.



## SPECIFICATIONS

### Dimensions:

- Available diameters 3"- 24"
- Available gauges 22, 20
- Standard pipe length is 5'
- 3"-12" = 22 gauge
- 13"-24" = 20 gauge

### Adjustable Sleeve Assembly:

Components include:

- Adjustable sleeve
- O-Ring (Black hollow center. -40°F to 250°F, BunaN, 60 Durometer)
- Clamp (Galvanized ASTM G90, Nitrile sponge adhered inside clamp, -104°F to 158°F)  
\*clamps ordered separately

### Material type:

- SMACNA, Galvanized ASTM A 653 and A924
- G60 galvanized steel (standard) & G90 upon request

### Pressure rating:

- CheetahDuct's typical design range is -2 to -28 wg

